



## **TD-401** 4-inch Desktop Thermal Label Printer

Express delivery labels | Industrial Labels | Retail and Supermarket Labels | Warehouse Management | Catering Labels | Apparel Tags



# 8 Core Strengths







#### **High-performance MCU control system**

**Memory function for** breakpoint reprinting

**High-speed and** high-quality printing





**Precision sensing** technology

Imported print head **Supports Bluetooth and** WiFi connection



Supports simultaneous connection and printing



Support for multiple languages

### Internal Large Space Easily accommodates large paper rolls

Visibility window for real-time monitoring of paper consumption

Waterproof | Dustproof | Stainproof



### **First Label Retraction Feature**

Paper automatically calibrates, not wasting a single label.



### Supports Computer Printing and Mobile printing

USB connection | WiFi connection | Bluetooth connection

Windows / MacOS / Linux

Android / IOS





## High-Speed and High-Quality Printing

150KM

Print Head Life

152/MM

Maximum Printing Speed

203DPI

**Printing Clarity** 



### Large Format Wide Printing

Maximum Print Width: 108mm

E 357

#### visible very grateful to your you usy read everything that is wo roud of yourself as it means

ND

- 11

AX108MM

Extra Large

### **2** TPL



King David 13875 Ramona Ave., Chino, CA 91710

content Description: TPL label printer Weight :280 grams Delivery date: January 1, 2023 Number of packages: 1



### **Compatible with Different Sizes of Thermal Labels**

### Easily handles a variety of printing needs



50mm

#### 40mm



### Applied to Multiple Industries All-encompassing printing solutions



**Express Delivery Labels** 



**Industrial Labels** 





**Retail and Supermarket Labels** 

Warehouse Management



**Catering Labels** 



**Apparel Tags** 

### **Printer Specificaton**

| Model                 | Desktop Barcode Printer TD-401                               |
|-----------------------|--------------------------------------------------------------|
| Print head dpi        | 203DPI                                                       |
| Printing method       | Thermal                                                      |
| Interface             | USB or USB+Bluetooth+WiFi                                    |
| Emulation             | TSPL、ZPL、CPCL、DPL、EPL                                        |
| Sensor                | Gap sensor/open cover sensor/Black label sensor              |
| Print speed           | 152mm/s (max)                                                |
| Printing width        | 108mm (max)                                                  |
| Printing length       | 1778mm (max)                                                 |
| SDRAM                 | SDRAM 8MB                                                    |
| FLASH                 | FLASH 8MB (expandable)                                       |
| Driver support system | Windows: Windows 7/10/11 (32 bit/64 bit)                     |
|                       | MacOS: 10.9/10.10/10.11/10.12/10.13/10.14/10.15/11.6/12.1/12 |
|                       | 12.3/12.4/14.4/14.6                                          |
|                       | Linux Ubuntu: 18.04/20.04/22.04/24.04                        |
|                       | Astra Linux Special Edition V1.6                             |
| APP support system    | Android 6.0 and above, iOS 11 and above                      |
| Bar code format       | Code128、EAN128、ITF、Code39、Code93、EAN13、EAN13+2、              |
|                       | EAN13+5、EAN8、EAN8+2、EAN8+5、CodeBar、Postnet、UPC-              |
|                       | UPC-A+2、UPC-A+5、UPC-E、UPC-E+2、UPC-E+5、MSI、MSIC、              |
|                       | PLESSEY、CPOST、ITF14、EAN14、Code11                             |
|                       |                                                              |

| Character enlargement/rotation              | 1-10x magnification /0°, 90°, 180°, 270° rotation/mirror printing                                                                                            |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Character                                   | GB18030、BIG5、ASCII                                                                                                                                           |
| Extended character                          | PC437、Katakana、PC850、PC860、PC863、PC865、West Europe、Greek、                                                                                                    |
|                                             | Hebrew、East Europe、Iran、WPC1252、PC866、PC852、PC858、IranII、                                                                                                    |
|                                             | Latvian、Arabic、PT151、PC747、WPC1257 and other languages, 61 kinds in total                                                                                    |
| Character size                              | 9x17dot, 12x24dot, 24x24dot                                                                                                                                  |
| Paper type                                  | Gap Label, Continuous Label, Black Mark Label, Folded Label                                                                                                  |
| Roll width<br>(including backing paper)     | 30~114mm                                                                                                                                                     |
| Roll thickness<br>(including backing paper) | 0.12~0.26mm                                                                                                                                                  |
| Paper axis size                             | 25.4mm                                                                                                                                                       |
| Roll outside diameter                       | 120mm (OD)                                                                                                                                                   |
| FEED                                        | Front exit                                                                                                                                                   |
| Power                                       | Input power supply: AC100 $\sim$ 240V, Output power: DC 24V~2.5A                                                                                             |
| Working environment                         | Operating temperature: 5~40°C                                                                                                                                |
|                                             | Operating humidity: 25~85%                                                                                                                                   |
| Storage environment                         | Storage temperature: -10~60°C                                                                                                                                |
|                                             | Storage humidity: 10~90%                                                                                                                                     |
| Print head life                             | 150km(Print rate 18.5%)                                                                                                                                      |
| Dimension                                   | 210 * 168.5 * 152.5 mm                                                                                                                                       |
| Weight                                      | 1.2KG                                                                                                                                                        |
| Accessories (standard)                      | <ol> <li>Power adapter 2. Power cord 3. USB cable 4. Quick installation Guide</li> <li>paper reel, paper roll baffle *2 6,Printing consumables *1</li> </ol> |
| Certification                               | CCC, CE, ROHS, REACH, TELEC (Japan), EAC (Russia), FAC (Russia), SRRC, BIS (Ind                                                                              |